



chemical solutions to concrete problems

QUICK RELEASE

GENERAL PURPOSE FORM RELEASE AGENT



Nox-Crete Quality at an Economical Price

If you are interested in both quality and value, we have you covered!
With Nox Crete's QUICK RELEASE you get a high-performing
petroleum-based form release agent at a value-engineered price point.

BENEFITS

- **Low odor:** No stink of reclaimed oil and no need for fruity perfumes typically used in low priced competitive products
- **Versatile Formulation:** Engineered to work with typical concrete mix designs, including those with Type 1L cement and pozzolans such as fly ash or blast-furnace slag
- **Positive, Crisp Release:** Ensures clean removal of forms, improving concrete finish quality
- **Reduces Maintenance Costs:** Build-up is kept to a minimum and forms become self-cleaning through repeated use
- **Durable in Various Conditions:** Resistant to foot traffic and rain, maintaining effectiveness under challenging site conditions
- **Cold Weather Application:** Good sprayability in cold temperatures, with a pour point of -30° F (-34° C)
- **Advanced Preparation:** Can be applied up to three weeks before the concrete pour, allowing for better scheduling flexibility
- **Non-Staining:** Will not stain concrete, ensuring that surfaces are ready for painting after proper preparation
- **Multiple versions available to meet all VOC requirements**



FOLLOW US



nox-crete.com • 1-800-669-2738

QUICK RELEASE: The cleaner, economical form release agent without the stink of reclaimed oil. Ensures crisp, positive release for better-looking concrete. Easily applied with standard low-pressure construction sprayers or optimized with higher pressure sprayers for maximum efficiency and performance.



QUICK RELEASE

- Mild odor
- Provides a crisp, positive release
- Resists wash-off
- Can be applied up to three weeks before concrete pour
- Meets all federal, state and Canadian VOC requirements



COMPETITIVE PRODUCTS

- Have a strong odor
- Can discolor cast concrete surfaces
- Are less effective

USAGE

- Easily applied with common construction sprayers
- Coverage rates on lumber and absorptive plywood surfaces (including MDO): 600-800 sf/gal (15-20 sm/L)
- Coverage rates on high-density overlaid plywood (HDO), steel and aluminum: 900-1250 sf/gal (22-31 sm/L)
- Also effective at combating existing concrete build-up, when applied immediately after stripping the forms

A cost-effective solution to concrete problems with superior Nox-Crete performance!

PACKAGING

- 275 gallon (1,040 L) totes
- 55 gallon (208 L) drums
- 5 gallon (19 L) pails



nox-crete.com • 1-800-669-2738

FOLLOW US

